SAFETY DATA SHEET

according to regulation of Europian parliament and Council (ES) number 1907/2006 according Committee regulation (EU) number 878/2020



10. 05. 2024 Date of Issue: Version number: No. of pages: 9

Revision date: Replaces version:

SANAKRYL ANTIKOR AK/MO Product name:

Section 1: Identification of substance/mixture and of the company/undertaking

The product is not a nanoform, nor does it contain any nanoforms.

UFI code: not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified use:

Product identifier:

1.1

Life cycle phases: PW (wide use by professionals - basic)

C (consumer use)

SANAKRYL ANTIKOR AK/MO

Usage Name: SU0

Other usage description: anticorrosive coating material

Market description: PC9a; PC15

Contributing Activity Name: roller or brush application

non-industrial spraying techniques

Contributing activities descriptor: PROC10 PROC11

More information: technical function of the product in anticorrosive coating material

this use:

0 - 10 t / yr quantity to use: Regulatory status by use: a limited number of devices for Nο

this use:

the subsequent period of use 24 months

relevant to this use:

ERC2; ERC8c; ERC8f; ERC10a;

an overview of environmental release categories for each life

FRC11a

cycle stage:

supplied as a mixture

1.2.2 Uses advised against: all other uses

Details of the supplier of the safety data sheet:

Producer and supplier: AUSTIS a. s.

Adress: K Austisu 680, 154 00 PRAHA 5 - Slivenec

Telephone number: +420 251 099 111 Fax: +420 251 099 112 austis@austis.cz e-mail

1.4 +420 725 491 378 Emergency telephone number: +420 251 099 247

Centre of the Toxicologicaly information Na Bojišti 1, 120 00 Prague 2, Tel.: +420 224 919 293

2. Section 2: Hazard identification

2.1 Classification of the substance or mixture The mixture is classified as dangerous for the environment.

Classification under Regulation 1272/2008/EU Aquatic Chronic 3; H412

2.2 Label elements

> Symbols: No symbols is used No signal word is used Signal word:

It contains a hazardous substance: trizinc bis(orthophosphate) and zinc oxide

Hazard Statement: H412: Harmful to aquatic life with long lasting effects.

P273: Avoid release to the environment. Precautionary Statement:

P501: Dispose of contents/container in accordance with relevant

national legislation.

2.3 Other hazards: The mixture does not meet criteria to be classified as PBT or vPvB

substances. The mixture is not endocrine disruptor, nor does it

contain any

Other risks: EUH208: It contains a reaction mixtue: CMIT/MIT (3:1) [Index number: 613-167-00-5]. May cause an allergic reaction.

Section 3: Composition / information on ingredients

1/9 SDS 36/2024

A mixture modified alkyd aqueous emulsions, pigments, fillers and additives. 3.2 Mixtures Chemical name: trizinc bis (orthophosphate) Content [%]: < 1.3 Index number: 030-011-00-6 CAS: 7779-90-0 EC number (EINECS): 231-944-3 **REACH Registration number:** 01-2119485044-40-00XX Classification according to Directive 1272/2008/EU: Aquatic Acute 1; H400 Aquatic Chronic 1, H410 M = 1 (acute) Specific concentration limits, M-factors: M = 1 (chronic) Chemical name: 2-butoxyethanol zinc oxide Content [%]: < 0.5 < 0.4603-014-00-0 030-013-00-7 Index number: CAS: 111-76-2 1314-13-2 EC number (EINECS): 203-905-0 215-222-5 **REACH Registration number:** 01-2119475108-36-00XX 01-2119463881-32-0XXX Classification according to Directive 1272/2008/EU: Acute Tox. 3; H331 Aquatic Acute 1; H400 Acute Tox. 4: H302 Aquatic Chronic 1; H410 Eye Irrit. 2; H319 Skin Irrit. 2; H315 Specific concentration limits. M-factors: inhalation: M = 1 (acute) ATE = 3 mg/l (vapour) M = 1 (chronic) oral. ATE = 1 200 mg/kg bw Established Exposure limit EH40/2005 (WELs): Chemical name: Mixture CMIT/MIT (3:1) Content [%]: < 0.0015 Index number: 613-167-00-5 55965-84-9 CAS: EC number (EINECS): 911-418-6 **REACH Registration number:** 01-2120764691-48-0XXX Classification according to Directive 1272/2008/EU: Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 **EUH071** Specific concentration limits, M-factors: Skin Corr. 1C; H314: C ≥ 0,6 % Eye Dam. 1; H318: C ≥ 0,6 % Skin Irrit. 2; H315: $0.06 \% \le C < 0.6 \%$ Eye Irrit. 2; H319: $0.06 \% \le C < 0.6 \%$ Skin Sens. 1A; H317: C ≥ 0.0015 % M = 100 (acute) M = 100 (chronic) This mixture contains ≥ 1 % titanium dioxide. The classification of Note: titanium dioxide according to Annex VI (as per Regulation (EC) No

Full text of H - phrases in Section 16

4. Section 4: First aid measures

4.1 Description of first aid measures

When providing first aid it is necessary to ensure safety of both victim and person rescuing. It is necessary to avoid chaotic behavior. Victim must be kept in mental and physical rest. Victim must be kept warm and must not get chilled. Take original container with label or safety data sheet with information about substance or mixture with you in case of medical examination.

Inhalation: Break exposure, move to fresh air protecting the victim from cold. Provide medical treatment especially if coughing, shortness of breath or other symptoms persist.

2/9 SDS 36/2024

1272/2008 of the European Parliament and of the Council) does not

apply to this mixture according to Note 10.

When on skin: Put away contaminated clothes and shoes, wash the contaminated spot with plenty of tepid water; if the skin is not irritated, soap can be used; seek doctor's advice, especially if the skin stays irritated.

Eye Contact: Rinse eyes with plenty of water (10 to 15 min). Keep eyes open (even by force if necessary). If the victim is wearing contact lenses remove them immediately. Seek medical attention.

Ingestion: Do not induce vomiting! Drink at least 0.5 liters of water with 5 to 10 tablets of crushed charcoal. In case of nausea contact the Toxicology Information Centre for need of medical treatment with information about composition of the mixture from the original container or SDS.

4.2 Most important symptoms and effects, both acute and delayed

The product may have adverse effects through inhalation and if swallowed. It can irritate skin, mucous membranes and eyes.

4.3 Indication of any immediate medical attention and special treatment needed:

Symptomatic treatment

5. Section 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media: The product is not inflammable. Water spray (water mist), foam, carbon dioxide, dry powder.

Unsuitable extinguishing media: The strong water current. It can be spread fire.

- 5.2 Specific danger linked to the substance or mixture: Carbon monoxide can be produced while burning.
- 5.3 Advice for firefighters: wear a breathing apparatus and protective clothing.

6. Section 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures: Appropriate protective gloves, goggles, appropriate clothing, or respirator.
- 6.1.1 For workers except for those intervening in emergency cases instructions in case of accidental spill and leak of substance or mixture:
 - a) use of appropriate protection (including personal protective equipment according to part 8 BL), in order to avoid any skin, eyes or personal clothing contamination;
 - b) removing possible sources of ignition, providing proper ventilation, control of dust not relevant
 - c) emergency measures, for example necessary evacuation from dangerous area or consultation with an expert not relevant
- 6.1.2 For workers intervening in emergency cases instructions for appropriate materials of personal protective suits (see part 8 BL)
- 6.2 Environmental precautions: Prevent environmental pollution leakage into drains, surface water, groundwater or soil.
- 6.3 Methods and materials for limitation of leaks and for cleaning:
- 6.3.1 Instructions for leak limitation of spilled substance or mixture
 - a) enclose the spilled mixture, cover the canalization;
 - b) seal the damaged package
- 6.3.2 Instructions for removal of spilled substance or mixture

Absorb with appropriate agent, hand over to authorized person for disposal.

6.4 Reference to other sections: See also section 7., 8 and 13.

7. Section 7: Handling and storage

- 7.1 Measures for safe manipulation:
- 7.1.1 Recomendations:
 - a) Workers handeling the product have to get familiar with health and safety rules for work and have to obey these rules. Secure escape routs (enclosing of leaked mixture, sealing of demaged packages and so on), for fire prevention (remove ignition sources, non-sparkling tools and so on) and limit the production of aerosol and dust.
 - b) Obey measures for prevention of manipulation with incompatible substances or mixtures (see part 10) in common areas.
 - c) Store in original closed packages in temperature from +5 to +25 °C, do not expose to temperature under 0 °C (not even in short term). Do not expose to direct sunlight or other heat sources.
 - d) Prevent the contamination of environment, i.e. leak into canalization, surface or underground water and soil.
- 7.1.2 Instructions for general hygiene of work:
 - a) Do not eat, drink or smoke on work areas.
 - b) After working with product wash your hands with soap and water, eventualy use regeneration hand cream.
 - c) Before entering dining areas, remove contaminated clothing and protective equipment.
- 7.2 Conditions for safe storage of substances and mixtures including incompatible substances and mixtures: Store in dry and well-ventilated storages in original closed packages in temperatures from +5 to +25 °C, do not expose to temperature under 0 °C (not even in short term). Do not expose to direct sunlight or other heat sources. Prevent any contact with oxidazing substances, strong acids and bases. Do not store with food, drinks and feed. The product is not a flamable liquid according to ČSN 65 0201.
- 7.3 Specific end use: see part 1.2; coating procedure and recomendations are listed in technical list of the product, or in other product documentation.

8. Section 8: Exposure controls / personal protection

8.1 Control parameters:

Exposure limits EH40/2005 (WELs):

Chemical name:

2-butoxyethanol

Long-term exposure limit [mg/m³] (TWA/8 h)

111-76-2 123 (25 ppm)

Short-term exposure limit [mg/m³] (15 minut)

246 (50 ppm)

3/9 SDS 36/2024

Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Trizinc bis(orthophosphate) (ES: 231-944-3)

DNEL (Workers, Hazard via inhalation route, Systemic effects, Long term 5 mg/m³

exposure)

DNEL (Workers, Hazard via dermal route, Systemic effects, Long term 83 mg/kg bw/day

exposure)

NOAEL (Workers, Hazard via dermal route, Systemic effects, Long term 83 mg/kg bw/day

exposure)

DNEL (General Population, Hazard via inhalation route, Systemic effects, 2,5 mg/m³

Long term exposure)

DNEL (General Population, Hazard via dermal route, Systemic effects, 83 mg/kg bw/day

Long term exposure)

NOAEL (General Population, Hazard via dermal route, Systemic effects, 83 mg/kg bw/day

Long term exposure)

DNEL (General Population, Hazard via oral route, Systemic effects, Long 0,83 mg/kg bw/day

term exposure)

NOAEL (General Population, Hazard via oral route, Systemic effects, 0,83 mg/kg bw/day

Long term exposure)

PNEC aqua (freshwater) 20,6 µg/L PNEC agua (marine water) $6,1 \mu g/L$ PNEC STP 100 μg/L

PNEC sediment (freshwater) 117,8 mg/kg sediment dw PNEC sediment (marine water) 56,5 mg/kg sediment dw PNEC soil 35,6 mg/kg soil dw

Zinc oxide [ES: 215-222-5]:

DNEL (Workers, Hazard via inhalation route, Systemic effects, Long term 5 mg/m³

exposure)

NOAEC (Workers, Hazard via inhalation route, Systemic effects, Long 5 mg/m³

term exposure)

DNEL (Workers, Hazard via inhalation route, Local effects, Long term 0,5 mg/m³

DNEL (Workers, Hazard via dermal route, Systemic effects, Long term 83 mg/kg bw/day

exposure)

NOAEL (Workers, Hazard via dermal route, Systemic effects, Long term 83 mg/kg bw/day

exposure)

DNEL (General Population, Hazard via inhalation route, Systemic effects, 2.5 mg/m³

Long term exposure)

NOAEC (General Population, Hazard via inhalation route, Systemic 2,5 mg/m³

effects, Long term exposure)

DNEL (General Population, Hazard via dermal route, Systemic effects, 83 mg/kg bw/day

Long term exposure)

NOAEL (General Population, Hazard via dermal route, Systemic effects, 83 mg/kg bw/day Long term exposure)

DNEL (General Population, Hazard via oral route, Systemic effects, Long 0,83 mg/kg bw/day

term exposure)

NOAEL (General Population, Hazard via oral route, Systemic effects, 0,83 mg/kg bw/day

Long term exposure)

PNEC aqua (freshwater) 20,6 µg/L

PNEC aqua (marine water) $6,1 \mu g/L$

PNEC STP 100 μg/L PNEC sediment (freshwater) 117,8 mg/kg sediment dw PNEC sediment (marine water) 56,5 mg/kg sediment dw

PNEC soil

2-butoxyethanol (ES: 203-905-0):

DNEL (Workers, Hazard via inhalation route, Systemic effects, Long term 98 mg/m³

exposure)

Acute/short term exposure)

DNEL (Workers, Hazard via inhalation route, Systemic effects, 1091 mg/m³

DNEL (Workers, Hazard via inhalation route, Local effects, Long term 246 mg/m³ (respiratory tract)

DNEL (Workers, Hazard via dermal route, Systemic effects, Long term 125 mg/kg bw/day

exposure)

NOAEL (Workers, Hazard via dermal route, Systemic effects, Long term 150 mg/kg bw/day

exposure)

4/9 SDS 36/2024

35,6 mg/kg soil dw

DNEL (Workers, Hazard via dermal route, Systemic effects, Acute/short 89 mg/kg bw/day

DNEL (General Population, Hazard via inhalation route, Systemic effects, 59 mg/m³

Long term exposure)

DNEL (General Population, Hazard via inhalation route, Systemic effects, 426 mg/m³

Acute/short term exposure)

DNEL (General Population, Hazard via inhalation route, Local effects, 147 mg/m³ (respiratory tract)

Long term exposure)

DNEL (General Population, Hazard via dermal route, Systemic effects, 75 mg/kg bw/day

Long term exposure)

NOAEL (General Population, Hazard via dermal route, Systemic effects, 150 mg/kg bw/day

Long term exposure)

DNEL (General Population, Hazard via dermal route, Systemic effects, 89 mg/kg bw/day

Acute/short term exposure)

DNEL (General Population, Hazard via oral route, Systemic effects, Long 6,3 mg/kg bw/day

term exposure)

DNEL (General Population, Hazard via oral route, Systemic effects, 26,7 mg/kg bw/day

Acute/short term exposure)

PNEC aqua (freshwater) 8,8 mg/L PNEC agua (marine water) 0,88 mg/L PNEC STP 463 mg/L

PNEC sediment (freshwater) 34,6 mg/kg sediment dw PNEC sediment (marine water) 3,46 mg/kg sediment dw PNEC soil 2,33 mg/kg soil dw PNEC oral (Hazard for predators) 0,02 g/kg food

8.2 Exposure controls

> Ensure adequate ventilation. Ensure protective equipment is worn while working with the product. Contaminated work clothes can be reused after thorough cleaning. Wash your hands and face with soap and water after use. Do not eat, drink or smoke while working with the product.

- 8.2.1 Appropriate engineering controls: Observe the usual precautions to protect the health and well-ventilated.
- 8.2.2 Individual protection measures, such as personal protective equipment:

Occupational exposure is governed by Directive 89/686/EEC therefore any use of personal protective equipment must be in accordance with

- a) Eyes and face protection: Suitable safety goggles (EN 166), face shiled.
- b) Skin protection: Common safety clothing with long sleave and shoes; take of the contaminated clothing and wash your skin with soap and water.
- b-1) Hands protection: suitable protective gloves (made from rubber according to EN 374), wash your hands with soap and water after work,
- c) Airways protection: with proper area ventilation not required. When spraying, face half-shiled is recomended for gass filtration (EN 405) or quarter-shiled with gass filter (EN 140, EN 141).
- d) Heat hazard: Special attention must be paid to construction of personal protective measures, when specifying protective measures for protection against materials, which are considered to be heat hazard. Not relevant for this product.
- 8.2.3 Environmental exposure controls: Avoid infiltration of surface and groundwater and soil.

9. Section 9: Physical and chemical properties

f) Combustibility:

9.1. Information on basic physical and chemical properties viscous liquid a) State

color shown on the cover b) Color

characteristic of acrylic dispersion c) Odour:

Odor threshold: Not specified approximately 0 d) Melting/Freezing point (temperature range) (°C): approximately 100

e) Boiling point or initial boiling point and boiling range (°C) non-flammable liquid

Not specified g) Explosion limints: upper limit (% volume): Not specified lower limit (% volume): Not specified h) Point of ignition: Not specified i) Temperature of self-ignition:

Not specified j) Temperature of decomposition (°C): 8,0 - 10,0 k) pH (23 °C) Not specified

I) Kinematic viscosity: m) Solubility (23 °C)

unlimited miscibility - with water Not specified - with fats:

Not specified n) Partition coefficient n - octanol/water:

2,3 kPa o) Steam pressure (20 °C): p) Density and/or relative density (20 °C): approximately 1,30 - 1,35 g.cm⁻³

q) Relative viscosity of steam (at °C): Not specified Not specified r) Particles characteristics:

> 5/9 SDS 36/2024

9.2 Other information:

9.2.1 Information about class of physical hazard: is not relevant

9.2.2 Other safety characteristics

Evaporation rate: Not specified Dynamic viscosity: Not specified Explosive properties: Not specified Oxidizing properties: Not specified

VOC (g/L) 15,2

10. Section 10: Stability and reactivity

Product is stable under recommended storage and handling conditions.

- 10.1 Reactivity: Product is not reactive under recommended storage and handling conditions.
- 10.2 Chemical stability: Product is stable under recommended storage and handling conditions.
- 10.3 Possibility of hazardous reactions: In case of contact with substances reacting dangerously with water.
- 10.4 Conditions to avoid: Temperatures below 0 °C and above 100 °C cause degradation of the product. Temperatures above recommended storage temperature reduce life of the product.
- 10.5 Incompatible materials: Substances reacting with water.
- 10.6 Hazardous Decomposition Products: Carbon monoxide may form during burning.

11. Section 11: Toxicological information

11.1 Information about hazard classes acording to (ES) č. 1272/2008

a) acute toxicity:

- LD₅₀, oral, rat (mg.kg⁻¹):

- LD₅₀, dermal, rat or rabbit (mg.kg⁻¹):

LC₅₀, inhalation, rat, for aerosols or particles (mg.kg⁻¹):

- LC₅₀, inhalation, rat, for gases and vapours (mg.kg⁻¹):

b) corrosivity/skin irritation:

c) serious eye damage / eyes irritation:

d) sensitivity of airways / sensitivity of skin:

e) germ cells mutagenicity:

f) carcinogenicity:

g) toxicity for reproduction:

h) toxicity for specific organs - single exposure:

i) toxicity for specific organs - multiple exposures:

j) hazards while inhaled:

Human experience:

Tests on animals: Were not performed

11.1.1 Information for each hazard class or breakdown:

11.1.2 Toxicological properties of mixture

2-butoxyethanol (ES: 203-905-0), Zinc oxide [ES: 215-222-5] and Trizinc see part 8

bis(orthophosphate) (ES: 231-944-3)

11.1.3 If enough information from substance/mixture trials exist, it might be necessary to sum up results of used studies, for example according to

exposure run

11.1.4 If the classification criteria are not met for specific hazard class, relevant concentration limits were not exceeded

information explaining the justification should be stated.

11.1.5 Information about likely exposure run

11.1.6 Symptoms corresponding to physical, chemical and toxicological features no effects on human health are known

11.1.7 Belated and immediate effects and chronical effects of short/long term no effects on human health are known

exposure

11.1.8 Interactive effects unknown 11.1.9 Lack of specific data not relevant 11.1.1(Mixtures see part 8

11.1.1 Mixtures information compared to substance information

1) Substances in the mixture can react with each other inside of a body and can cause different levels of absorption, metabolism and secretion.

2) It is necessary to consider, if concentration of each substance is sufficient to contributeto mixture's effects on health. For each substance

6/9

a) if the information are doubled, they are listed only once for a substance as a whole, for example when two different substances are causing vomiting and diarrhea;

Not relevant for this mixture.

b) if it is not likely the effects will appear with current concentrations, for example when weak irritating substance is disolved in non-irritating solution to a level under certain concentration;

SDS 36/2024

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information.

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information.

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information.

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information.

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information

the classification cirteria are not met based on avilable information

No detrimental effects were found upon compliance with the

Not relevant for this mixture.

no effects on human health are known

prescribed safety measures.

see above

not avilable

not relevant

c) if the information about mutual effects of substances in the mixture are see part 8 unavilable, no assumptions will be listed and instead effects on healtf of

each substance will be listed.

11.1.12 Other information

12.2

12.5

12.7

None

11.2 Other hazards information

11.2.1 Features causing disruption of endocrinal systém

Not relevant for this mixture.

11.2.2 Additional data: None

12. Section 12: Ecological information

Results of PBT and vPvB

12.1 Toxicity Harmful to aquatic life with long lasting effects.

Acute toxicity for water organisms: **Mixture** - LC₅₀, 96 hours, fish (mg/kg): Not set - LC₅₀, 48 hours, fish (mg/kg): Not set - IC₅₀, 72 hours, algae (mg/kg): Not set Persistence and degradability: Not set

12.3 Bioaccumulative potential: Not set

Mobility in soil: 12.4 It was not determined, the blend is miscible with water.

The mixture does not meet the criteria for classification as PBT or

vPvR

12.6 Features causing disruption of endocrinal systém Unknown for this mixture

Other adverse effects: See Section 2

Additional data: Details on the toxicity of hazardous components are given below.

Toxicity Data for Hazardous components

Component	trizinc bis (orthophosphate)	Zinc oxide
CAS number	7779-90-0	1314-13-2
Toxicity to algae	NOEC = 60 μg/L (72 h)	EC ₁₀ = 84 μg/L (72 h) NOEC = 4,9 μg/L (72 h)
Toxicity to fish	LC ₅₀ = 166 μg/L (96 h)	LC ₅₀ = 439 μg/L (96 h)
Toxicity to water fleas	LC ₅₀ = 1220 μg/L (48 h) EC ₅₀ = 860 mg/L (48 h)	LC ₅₀ = 1220 μg/L (48 h) EC ₅₀ = 860 mg/L (48 h)

13. Section 13: Disposal considerations

13.1 Methods of waste management:

(a) Appropriate methods of disposal of the substance or mixture and contaminated packaging: Risk of environmental contamination, follow the Waste Act (as amended) and the applicable Waste Disposal Regulations (as amended). Place the unused product and contaminated packaging in marked waste collection containers and hand it over for disposal to an authorised waste disposal person (specialised company) authorised to do so. Do not dispose of unused product down the drain. It must not be disposed of with municipal waste. Empty packaging may be used for energy recovery in a waste incinerator (except for metal) or disposed of in a landfill of the appropriate classification. Completely cleaned packaging may be handed over for recycling. Always comply with the relevant national legislation!

- Translated with www Deenl com/Translator (free version) b) Physical / chemical properties that can affect means of waste handling: Liquid mixture is completely miscible with water.
- c) Avoidance of disposal through sewer: It is necessary to prevent leakage of both components and hardened mixture into drains.
- d) Special precautions for the recommended waste management: Avoid contact with skin and eyes.

14.	Section 14: Transport information		
14.1	UN number or ID number	Not specified	
	Required shipping label:		
	ADR/RID/ADN:	Not specified	
	IMDG:	Not specified	
	ICAO TI:	Not specified	
14.2	Proper name of the United Nations for the shipment		
	Ground transport ADR/RID/ADN:	Not specified	
	Naval transport IMDG:	Not specified	
	Air transport ICAO TI:	Not specified	
14.3	Transport hazard class(es):		
	ADR/RID/ADN:	Not specified	
	IMDG:	Not specified	
	ICAO TI:	Not specified	
14.4	Packing group:		
	ADR/RID/ADN:	Not specified	
	IMDG:	Not specified	
	ICAO TI:	Not specified	
14.5	Environmental hazards:	Not specified	
•			

7/9 SDS 36/2024 Special precautions for user: See Section 8Special provisions (ADR): Not specified

14.7 Naval mass-transport according to instrumenst IMO: Not applicable

Notes: None Additional data: None

15. Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Regulation of the European Parliament and Council Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals establishing a European Chemicals Agency, as amended

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 (CLP) as amended

Commision directive (EU) No. 878/2020

EH40/2005 Workplace exposure limits (second edition, published 2011). Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended)

Were not performed

15.2 Assessment chemical safety of mixture:

16. Section 16: Other informations

Information stated in this safety data sheet is based on the current knowledge of EU legislation. It is recommendation in terms of health and safety as well as recommendation related to ecological matters that are essential to safe usage of the product.

a) New edition.

b) key or legend for abbreviations and accronyms used in the safety data sheet:

LD₅₀ The lethal dose for 50 % mortality of the test population relative to a control sample.

LC₅₀ Lethal concentration for 50 % mortality of the test population relative to a control sample.

EC₅₀ Effective concentration for 50 % mortality of the test population relative to a control sample.

EC₁₀ Effective concentration for 10 % mortality of the test population relative to a control sample.

IC₅₀ Inhibitory concentration to reduce the growth or growth rate of 50% of the test population relative to a control sample.

LL₅₀ Lethal loading doses of test substance resulting in 50% mortality

EL₅₀ Effective loading doses of test substance resulting in 50% mortality

PBT Persistent, bioaccumulative and toxic substances.

vPvB Very persistent and very bioaccumulative substances.

DNEL Derived No Effect Level - derived concentration of the substance without adverse effects

DMEL Derived Minimum Effect Level - derived minimum level at which the adverse effects

NOAEL No Observed Adverse Effect Level - no negative effect was observed

PNEC Predicted No Effect Concentration - an estimate of the concentration of the substance without adverse effects

NOELR No Observed Effect Loading Rate - dosage rate without observed effect NOEC No Observed Effect Concentration - concentration without observed effect

NOEL No Observed Effect Level - level without observed effect

LOEC Lowest Observed Effect Concentration - lowest concentrations with observable effects

ADR European Agreement concerning the international carriage of dangerous goods by road.

RID Regulations concerning the international carriage of dangerous goods by rail.

IMDG International maritime code of dangerous goods.ICAO The International Civil Aviation Organization.IATA International Air Transport Association.

GHS Globally Harmonized System of Classification and Labelling of Chemical substances.

c) important references to literature and data sources

Initial data sources are safety data sheets of the inherent (components).

d) in case of mixture, statement about evaluation method used for classification according to article 9 of directive (ES) number 1272/2008

For evaluation purposes, principles of extrapolation were used. Calculation methods.

e) List of H-sentences, whose full form is not listed in other parts.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H330 Fatal if inhaled.

8/9 SDS 36/2024

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH071 Causes burns to the respiratory tract.

Guidelines for training:

As required by national legislation.

Recommended restrictions on use (i. e. non-statutory recommendations by supplier):

Product should not be used for other purposes than specified (see section 1.2). Because specific conditions of use are beyond supplier's control it is responsibility of the user to adapt notifications to local law and regulations. Safety information describe the product with regard to safety and can not be considered technical information about the product.

9/9 SDS 36/2024